

H3000

4X2 Enhanced Edition Prime Mover



H3000

6X4 Enhanced Edition Prime Mover



HS HANVAN COMMERCIAL VEHICLES SDN. BHD.

SHOWROOM

**PMT 1280, Lorong Perusahaan Sg. Lokan 3,
Kawasan Perusahaan Sg. Lokan 13800 B.W.**

Tel: 04-356 7668 Fax: 04-356 7669

www.hsg.com.my

SHACMAN H3000 Enhanced Edition Prime Mover Series

Model		SX4185GT361R	SX4185GV321R	SX4255GV324R
Driven type	Driven type	4x2	6x2	6x4
Weight	Curb Weight (kg)	7250	9350	9650
	GCW (kg) (Technical)	50000	60000	90000
Dimensions	Wheel Base (mm)	3600	3175+1400	3175+1400
	Length (mm)	6120	6825	6825
	Width (mm)	2490		
	Height (mm)	3550 (Cabin with shroud 3880)		
	Front Overhang (mm)	1525		
	Rear Overhang (mm)	995	725	
Performance	Economic / Max. Speed(km/h)	60-85 / 115		55-80 / 110
	Max. Grade Ability (%/°)(GCW)	25%/14°		24%/13°
Core Equipments Specifications				
Engine	Type	In-line, 6 cylinder, water cooling, 4-stroke, Direct Injection, turbocharging, intercooling		
	Model	WP12.375N	WP12.430N	
	Rated Power/Speed(KW/r/min)	375HP(276kW)/1900rpm	430HP(316kW)/1900rpm	
	Max.Torque /Economic speed	1800N.m/1000-1400rpm	2060N.m/1000-1400rpm	
	Displacement (L)	11.596L		
Clutch	Model / Type	φ430 / Single plate, diaphragm spring		
Transmission	Brand	FAST		
	Model	12JSD200TA-with air assist	16JSD200TA-with air assist	
	Max. Torque(Nm)	2000N.m		
	Gears	12 Forward shift+2 Reverse shift	16 Forward shift+2 Reverse shift	
Frame	Type	850×270 (8+5)	850×300 (8+5)	
Axle	Brand	Hande		
	Front	7.5T MAN		
	Rear	13T MAN double reduction axle	16T MAN double reduction axle	
Suspension	Type	Front less and rear multi leaf springs	Front less and rear multi leaf springs, rear hydraulic lift axle	Front less and rear multi leaf springs, four main Springs + four U-bolts
The Fifth Wheel	Type	JOST-50#(with E-Mark)		
Steering Gear	Type	Integral circulating ball power steering		
Brake System	Wheel Brake	Drum brake		
Fuel Tank	Capacity(L)	600L(Aluminium alloy)		
Tires	Type	295/80R22.5		
Electrical	Batteries	165Ah Maintenance-free		
Standard Equipments Specifications				
Others	Cab	H3000 lengthened and high roof cabin		
	Equipment	Cab top side shroud, auto-adjustable air-conditioner, air main seat, hydraulic auxiliary seat, four point air suspension, electric window lifter, highway bumper, three-level boarding pedal, oil pan protective grille and aluminum alloy air reservoir.		
		Optional:Hydraulic retarder, ABS, rear axle speed ratio:4.266/4.769/5.262/5.92/6.733		

