

HOHAN NX PRIME MOVER



HOHAN NX-MC (EURO 5) SPECIFICATION

Drive Line		4x2	6x2	6x4
Weight	GVW (Kg)	18000	25000	25000
	Kerb Weight (Kg)	6800	8800	8800
Dimensions	Overall Dimension	6175x2550x3500	6865x2550x3500	6850x2550x3500
	Wheel Base	3600	3225+1365	3225+1350
	Front/Rear wheel track (mm)	2030/1830	2040/1850	2040/1850
	Front/Rear overhang (mm)	1550/1025	1550/2965	1550/725
	Approach/Departure angle (°)	14/28	17/15	12/14
Performance	Max. speed (km/h)	119	119	112
	Max. gradeability(%)	30	30	30
	Minimum turning diameter (m)	17	18	18
Engine	Model	MC11.44-50		MC13.54-50
	Horsepower (Hp)	440		540
	Maximum output Kw/r/min	324/1900		400/1900
	Maximum torque N.m/r/min	2100/1000-1400		2500/1000-1400
	Type	4 stroke high pressure common rail diesel engine, 6 cylinder in-line with water cooling, supercharging intermediate cooler		
	Borex Stroke	120x155mm		126x166mm
	Valve	4		
Displacement(L)		10.518		12.419
Transmission		Model : HW25716XACL, AMT Type : WABCO Transmission Control System, 16 forward and 4 reverse		Model : HW25712XST(CL), Manual Type : 12 forward and 2 reverse
Cabin		Model : H78L-R Low Roof Type : 4 point Air suspension Cabin, Air cushioned driver seat, Automated Air-conditioning, Daytime Running Light, Electrical Cabin Lifting, Dual-tone air horn, 7 inch MP5, Power Window		
Clutch		Model : CH430-21, Type : Diameter 430mm diaphragm spring clutch		
Steering		Model : ZF8098, Type : Steering hydraulic steering with power assistance		
Front Axle		Model : VGD71, Type : Forging I-beam front axles equipped with drum brake, Loading capacity = 7100Kg		Model : VGD95, Type : Forging I-beam front axles equipped with drum brake, Loading capacity = 9500Kg
Rear Axles		Model : MCY13JGS Type : central single reduction, drum brake, Loading capacity : 13000, ratio : 3.7		Model : MCP16ZG Type : central + hub reduction, drum brake, Loading capacity : 2x16000 ratio : 4.2
Suspension	Front	3 or 9pcs Semi-elliptical leaf springs with shock absorbers and stabilizer		9 pcs Semi-elliptical leaf springs with shock absorbers and stabilizer
	Rear	4 pcs air bag or 9+6 pcs Bogie leaf springs with divided balance shaft and stabilizer		5 layer parabolic leaf springs with shock absorbers and stabilizer Hydraulic Lift
Brake System	Service brake	Dual circuit compressed air brake		
	Parking brake	Spring storage energy without air		
	Auxilliary brake	Engine exhaust brake		
Rim/s Tyres		22.5x9.00 /295/80R22.5		
Electrics		Voltage: 24V; Batteries: 2x12V,180AH		
Fuel Tank		Aluminium fuel tank with locking fuel cap Capacity : 600L		Aluminium fuel tank with locking fuel cap Capacity : 400L
Others		Aluminium fuel tank with locking fuel cap Capacity : 600L		



HS HOHAN COMMERCIAL VEHICLES SDN. BHD.

SHOWROOM

**PMT 1280, Lorong Perusahaan Sg. Lokan 3,
Kawasan Perusahaan Sg. Lokan 13800 B.W.**

Tel: 04-356 7668 Fax: 04-356 7669

www.hsg.com.my

HOHAN NX TIPPER TRUCK



HOHAN NX TIPPER (EURO 5) SPECIFICATION

Drive Line		6x4	8x4
Weight	GVW (Kg)	25000	31000
	Kerb Weight (Kg)	9900	10500
	Wheel Base	4200+1350 / 4600+1350 / 5000+1350	
	Front/Rear wheel track (mm)	2040/1850	
	Front/Rear overhang (mm)	1550/1000	
	Approach/Departure angle (°)	27/45	
		16/18	
Performance	Max. speed (km/h)	77	
	Max. gradeability(%)	30	
	Minimum turning diameter (m)	23	
Engine	Model	WP10.380E53	
	Horsepower (Hp)	380	
	Maximum output Kw/r/min	280/1900	
	Maximum torque N.m/r/min	1630/1200-1500	
	Type	4 stroke high pressure common rail diesel engine, 6 cylinder in-line with water cooling, supercharging intermediate cooler	
	Borex Stroke	126x130mm	
	Valve	4	
Displacement(L)	9.726		
Transmission		Model : HW19709XST, MT Type : 9 forward and 1 reverse	
Cabin		Model : H77L-R Low Roof Type : 4 point Air suspension Cabin, Spring cushioned driver seat, Automated Air-conditioning, Daytime Running Light, Electrical Cabin Lifting, Dual-tone air horn, MP3, Power Window	
Clutch		Model : CH430-21, Type : Diameter 430mm diaphragm spring clutch	
Steering		Model : ZF8098, Type : Steering hydraulic steering with power assistance	
Front Axle		Model : VGD95, Type : Forging I-beam front axles equipped with drum brake, Loading capacity = 9500Kg	
Rear Axles		Model : MCP16ZG Type : central + hub reduction, drum brake, Loading capacity : 2x16000 ratio : 4.77	
Suspension	Front	10 pcs Semi-elliptical leaf springs with shock absorbers and stabilizer	
	Rear	12 pcs Bogie leaf springss with divided balance shaft and stabilizer	
Brake System	Service brake	Dual circuit compressed air brake	
	Parking brake	Spring storage energy without air	
	Auxilliary brake	Engine exhaust brake	
Rim/s Tyres		22.5x9.00 /295/80R22.5	
Electrics		Voltage: 24V; Batteries: 2x12V,180AH	
Fuel Tank		Aluminium fuel tank with locking fuel cap Capacity : 400L	



HS HOHAN COMMERCIAL VEHICLES SDN. BHD.

SHOWROOM

**PMT 1280, Lorong Perusahaan Sg. Lokan 3,
Kawasan Perusahaan Sg. Lokan 13800 B.W.**

Tel: 04-356 7668 Fax: 04-356 7669

www.hsg.com.my

HOHAN NX MIXER TRUCK



HOHAN NX MIXER (EURO-5) SPECIFICATION

Drive Line		6x4
Weight	GVW (Kg)	25000
	Kerb Weight (Kg)	8800
Dimensions	Overall Dimension	8800x2550x3150
	Wheel Base	4200+1350
	Front/Rear wheel track (mm)	2040/1850
	Front/Rear overhang (mm)	1550/1700
	Approach/Departure angle (°)	27/17
	Performance	Max. speed (km/h)
	Max. gradeability(%)	30
	Minimum turning diameter (m)	18.5
Engine	Model	WP10.380E53
	Horsepower (Hp)	380
	Maximum output Kw/r/min	280/1900
	Maximum torque N.m/r/min	1630/1200-1500
	Type	4 stroke high pressure common rail diesel engine, 6 cylinder in-line with water cooling, supercharging intermediate cooler
	Borex Stroke	126x130mm
	Valve	4
	Displacement(L)	9.726
Transmission		Model : HW19709XST, MT Type : 9 forward and 1 reverse
Cabin		Model : H77L-R Low Roof Type : 4 point Air suspension Cabin, Spring cushioned driver seat, Automated Air-conditioning, Daytime Running Light, Electrical Cabin Lifting, Dual-tone air horn, MP3, Power Window
Clutch		Model : CH430-21, Type : Diameter 430mm diaphragm spring clutch
Steering		Model : ZF8098, Type : Steering hydraulic steering with power assistance
Front Axle		Model : VGD95, Type : Forging I-beam front axles equipped with drum brake, Loading capacity = 9500Kg
Rear Axles		Model : MCP16ZG Type : central + hub reduction, drum brake, Loading capacity : 2x16000 ratio : 4.77
Suspension	Front	9 pcs Semi-elliptical leaf springs with shock absorbers and stabilizer
	Rear	12 pcs Bogie leaf springss with divided balance shaft and stabilizer
Brake System	Service brake	Dual circuit compressed air brake
	Parking brake	Spring storage energy without air
	Auxilliary brake	Engine exhaust brake
Rim/s Tyres		22.5x9.00 /295/80R22.5
Electrics		Voltage: 24V; Batteries: 2x12V,180AH
Fuel Tank		Aluminium fuel tank with locking fuel cap Capacity : 300L
Others		



HS HOHAN COMMERCIAL VEHICLES SDN. BHD.

SHOWROOM

**PMT 1280, Lorong Perusahaan Sg. Lokan 3,
Kawasan Perusahaan Sg. Lokan 13800 B.W.**

Tel: 04-356 7668 Fax: 04-356 7669

www.hsg.com.my

HOHAN NX CARGO TRUCK



HOHAN NX-CARGO (EURO 5) SPECIFICATION

Drive Line		4x2
Weight	GVW (Kg)	19000
	Kerb Weight (Kg)	7050
Dimensions	Overall Dimension	10050 x 2550 x 3020
	Wheel Base	5600/6250/6400/6880/7100/7380
	Front/Rear wheel track (mm)	2046/1860
	Front/Rear overhang (mm)	1550/3100
	Approach/Departure angle (°)	15/14
Performance	Max. speed (km/h)	90
	Max. gradeability(%)	30
	Minimum turning diameter (m)	27
	Model	MC07.31-50
Engine	Horsepower (Hp)	310
	Maximum output Kw/r/min	225/2300
	Maximum torque N.m/r/min	1218/1200-1800
	Type	4 stroke high pressure common rail diesel engine, 6 cylinder in-line with water cooling, supercharging intermediate cooler
	Borex Stroke	108x125mm
	Valve	4
	Displacement(L)	6.87
Transmission		Model : HW15710AC, AMT Type : WABCO Transmission Control System, 10 forward and 2 reverse Model : HW19709XST, MT Type : 9 forward and 1 reverse
Cabin		Model : H77L-R Low Roof Type : 4 point Air suspension Cabin, Air cushioned driver seat, Automated Air-conditioning, Daytime Running Light, Electrical Cabin Lifting, Dual-tone air horn, MP3, Power Window
Clutch		Model : CH430-15A, Type : Diameter 430mm diaphragm spring clutch
Steering		Model : ZF8098, Type : Steering hydraulic steering with power assistance
Front Axle		Model : VGD71, Type : Forging I-beam front axles equipped with drum brake, Loading capacity = 7100Kg
Rear Axles		Model : MCJ11BGY Type : central single reduction, drum brake, Loading capacity : 13000, ratio : 3.7
Suspension	Front	7 pcs Semi-elliptical leaf springs with shock absorbers and stabilizer
	Rear	7+3 pcs Bogie leaf springs with divided balance shaft and stabilizer
Brake System	Service brake	Dual circuit compressed air brake
	Parking brake	Spring storage energy without air
	Auxilliary brake	Engine exhaust brake
Rim/s Tyres		22.5x9.00 /295/80R22.5
Electrics		Voltage: 24V; Batteries: 2x12V,180AH
Fuel Tank		Aluminium fuel tank with locking fuel cap Capacity : 300L



HS HOHAN COMMERCIAL VEHICLES SDN. BHD.

SHOWROOM

**PMT 1280, Lorong Perusahaan Sg. Lokan 3,
Kawasan Perusahaan Sg. Lokan 13800 B.W.**

Tel: 04-356 7668 Fax: 04-356 7669

www.hsg.com.my