

HOHAN NX TIPPER TRUCK



HOHAN NX TIPPER (EURO 5) SPECIFICATION

Drive Line		6x4	8x4
Weight	GVW (Kg)	25000	31000
	Kerb Weight (Kg)	9900	10500
	Wheel Base	4200+1350 / 4600+1350 / 5000+1350	
	Front/Rear wheel track (mm)	2040/1850	
	Front/Rear overhang (mm)	1550/1000	
	Approach/Departure angle (°)	27/45	
	Minimum turning diameter (m)	16/18	
Performance	Max. speed (km/h)	77	
	Max. gradeability(%)	30	
	Minimum turning diameter (m)	30.5	
Engine	Model	D10.38-50	
	Horsepower (Hp)	380	
	Maximum output Kw/t/min	274/2000	
	Maximum torque N.m/t/min	1560/1200-1500	
	Type	4 stroke high pressure common rail diesel engine, 6 cylinder in-line with water cooling, supercharging intermediate cooler	
	Borex Stroke	126x130mm	
	Valve	4	
Displacement(L)	9.726		
Transmission		Model : HW19709XST, MT Type : 9 forward and 1 reverse	
Cabin		Model : H77L-R Low Roof Type : 4 point Air suspension Cabin, Spring cushioned driver seat, Automated Air-conditioning, Daytime Running Light, Electrical Cabin Lifting, Dual-tone air horn, MP3, Power Window	
Clutch		Model : CH430-21, Type : Diameter 430mm diaphragm spring clutch	
Steering		Model : ZF8098, Type : Steering hydraulic steering with power assistance	
Front Axle		Model : VGD95, Type : Forging I-beam front axles equipped with drum brake, Loading capacity = 9500Kg	
Rear Axles		Model : MCP16ZG Type : central + hub reduction, drum brake, Loading capacity : 2x16000 ratio : 4.77	
Suspension	Front	10 pcs Semi-elliptical leaf springs with shock absorbers and stabilizer	
	Rear	12 pcs Bogie leaf springss with divided balance shaft and stabilizer	
Brake System	Service brake	Dual circuit compressed air brake	
	Parking brake	Spring storage energy without air	
	Auxilliary brake	Engine exhaust brake	
Rim/s Tyres		22.5x9.00 /295/80R22.5	
Electrics		Voltage: 24V; Batteries: 2x12V,180AH	
Fuel Tank		Aluminium fuel tank with locking fuel cap Capacity : 400L	



HS HOHAN COMMERCIAL VEHICLES SDN. BHD.

SHOWROOM
PMT 1280, Lorong Perusahaan Sg. Lokan 3,
Kawasan Perusahaan Sg. Lokan 13800 B.W.
Tel: 04-356 7668 Fax: 04-356 7669
www.hsg.com.my