

SINOTRUK C3H HOHAN SERIES



SINOTRUK

"Building Trust, Delivering Excellence"

TECHNICAL SPECIFICATION

| MODEL CODE | | | ZZ1097C3HC38V | ZZ1097C3HC38V1 | ZZ1097C3HC38W | ZZ1097C3HC38X | |
|---------------------|--------------------------|--------------------|---|----------------|---------------|---------------|--|
| DRIVE TRAIN | | | 4X2 | | | | |
| DIMENSIONS | Overall Length | mm | 6852 | 7480 | 7930 | 8455 | |
| | Overall Width | mm | 2600 | | | | |
| | Overall Height | mm | 2438 | | | | |
| | Wheelbase | mm | 3850 | 4200 | 4500 | 4850 | |
| | Front Tread | mm | 1806 | | | | |
| | Rear Tread | mm | 1800 | | | | |
| | Minimum ground clearance | mm | 244 | | | | |
| | Approach angle | ° | 14 | | | | |
| | Departure angle | ° | 9 | | | | |
| Front overhang | mm | 1180 | | | | | |
| Rear overhang | mm | 1759 | 2100 | 2250 | 2425 | | |
| ENGINE | Make & model | | CUMMINS ISF3.8S5154 | | | | |
| | Type | | Diesel, Turbocharged, Inter-cooled, Four-Stroke | | | | |
| | Total displacement | L | 3.8 | | | | |
| | Rating power | KW(r/min) | 115/2600 | | | | |
| | Maximum torque | Nm(r/min) | 491/1200~1900 | | | | |
| Emission level | | Euro 5 | | | | | |
| TRANSMISSION | Model | | WLY6G55 | | HW51508ACL | | |
| | Type | | Manual 6-speed | | AMT 8-speed | | |
| | Forward speed ratio | 1st | | 6.198 | 9.03 | | |
| | | 2nd | | 3.287 | 5.89 | | |
| | | 3rd | | 2.224 | 4.34 | | |
| | | 4th | | 1.371 | 3.31 | | |
| | | 5th | | 1 | 2.08 | | |
| | | 6th | | 0.78 | 1.36 | | |
| | | 7th | | | 1 | | |
| | | 8th | | | 0.76 | | |
| Reverse speed ratio | R1 | | 5.681 | 8.52 | | | |
| | R2 | | | 1.96 | | | |
| WEIGHT | Gross vehicle weight | kg | 7500 | | | | |
| | Curb weight | kg | 3030 | 3050 | 3070 | 3090 | |
| | Front axle | kg | 2090 | 2090 | 2090 | 2090 | |
| | Rear axle | kg | 940 | 960 | 980 | 1000 | |
| PERFORMANCE | Maximum driving speed | km/h | 90 | | | | |
| | Minimum turning diameter | M | 14.5 | | | | |
| | Maximum gradability | % | 30 | | | | |
| | Maximum parking slope | % | 15 | | | | |
| | Fuel tank capacity | L | 150 | | | | |
| BRAKES | Rating pressure | kPa | 850 | | | | |
| | Type of service brake | | Dual-circuit air pressure brake | | | | |
| | Braking force adjustment | | ABS+ASR | | | | |
| | Type of parking brake | | Spring storage energy without air | | | | |
| SUSPENSION | Front | Type | Non-independent | | | | |
| | | No. of Leaf Spring | 8 | | | | |
| | Rear | Type | Non-independent | | | | |
| | | No. of Leaf Spring | 9+6 | | | | |
| ELECTRICAL | Batteries | V/Ah | 24/105 | | | | |
| | Alternator | kW | 1.96 | | | | |

SAFE AND HIGH-END INTERIOR TRIMS



Digital display and electrically adjustable A/C



Quiet cab



D-shaped multi-functional steering wheel



12.3-inch colour-screen instrument



Luxury courtesy light



Cloud like luxury seats



334mm extra-wide boarding step



12.8-inch suspended smart screen



Reverse camera & buzzer



Electricity control windows & side view mirror



SINOTRUK Smart Link - Intelligent vehicle's management system

APPLICATION OF C3H SERIES MODEL



Light-duty bus



Van



Refrigerator truck



Oil tanker



Dropside truck



Stake truck

Note : 1. Prices, specifications & accessories are subjected to change without prior notice.

2. Product image for illustration purposes only. Actual product may vary.



HS HOHAN COMMERCIAL VEHICLES SDN BHD (0966040-A)

Showroom

PMT 1280, LORONG PERUSAHAAN SUNGAI LOKAN 3, KAWASAN PERUSAHAAN SUNGAI LOKAN, 13800 BUTTERWORTH, PENANG, MALAYSIA.

Tel : 04- 356 7668

Fax : 04-356 7669

www.hsg.com.my